



Solar Lighting Australia



LED Canopy Light – 200W

Model: SLA-C200W

Surface mount LED canopy lights are suitable for both outdoor and indoor commercial applications such as loading docks, petrol stations, freezers, cool rooms, food processing plants and common areas.

Product Features

- Only consumes 200w of power
- Aluminium die cast housing
- Opal polycarbonate face
- Long operating life and performance
- 120° Beam Angle
- IP54 Waterproof housing
- Easy connect junction box on rear



SPECIFICATION

Colour	Cool White (6000K)
Lumen (lm)	20000lm
LED Efficiency (Lm/w)	>140lm/w
Light Source	Philips 3030 LED's
CRI (%)	>80%
Beam Angle	120°
Power Requirement	AC 100~240V
Power Consumption	200W
Housing	Die Cast Aluminium and Opal PC Lens
Lifespan	> 40,000 hours
Operation Temperature	-20°C~+45°C
Dimension (mm)	580 (L) × 580 (W) × 120 (D)
Weight	11.2kg
Protection Rating	IP54
Warranty	5 years

Solar Lighting Australia. 1/13 Commerce Circuit, Yatala Qld 4207

Telephone: 1300 911 866

Website: solarlightingaustralia.com

Email: sales@solarlightingaustralia.com